

红大洋实业(深圳)有限公司

Rubysun Industrial(Shenzhen) Electronics Co.,Ltd

承 认 书**APPROVING SHEET**

CUSTOMER

客 户: _____

PART NAME : Chip-Aluminum Electrolytic Capacitor

品 名: 片式铝电解电容器

SERIES:

系 列: VT

SPECIFICATION:

规格: 全系列规格书

DATE

日 期: 2017-10-18

制 造 MANUFACTURE		客 户 CUSTOMER	
拟 制 FORMULATE	批 准 APPROVAL	检 验 CHECK	批 准 APPROVAL
施华	黄应明		

地址: 深圳市福田区上步工业区 1 号厂房第五层

电话(TEL): 13691683518 0755-83227006

传真(FAX): 0755-83221895

邮编(POST CODE):

E-mail:

序号 No	目录 INDEX	页 page
1	概述 SCOPE	3
2	外形尺寸图及尺寸表 Case size table	3
3	技术性能 SPECIFICATIONS	4
4	称电容量、额定电压、额定纹波电流与外形尺寸对应表 Nominal capacitance, rated voltage, rated ripple current and case size table	5
5	构造图及材料表 Frame drawing and materials	6
6	试验方法及要求 TESTS	7-10
7	标志 Marking	11
8	片式铝电解电容的编带 V- Chip Type Aluminum Electrolytic Capacitors	12


一、概述 SCOPE

本产品规格书适用于红太洋实业(深圳)有限公司 CDVT 型片式铝电解电容器产品。


The product specification is adapted to series CDVT V-CHIP Aluminum Electrolytic Capacitors of CHANGZHOU JIARONG ELECTRONIC CO., LTD.

二、外形图及尺寸表 Case size table

1. $\phi 4 \sim \phi 6.3$



2. $\phi 8 \sim \phi 18$



单位:mm

	4×5.4	5×5.4	6.3×5.4	6.3×7.7	6.3×10.5	8×10.5	8×12.5	10×10.5	10×12.5	12.5×13.5	12.5×16.5	16×16.5	18×16.5	18×21.5
A	1.8	2.1	2.4	2.4	2.4	2.9	2.9	3.2	3.2	4.8	4.8	5.8	6.8	6.8
B	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3	10.3	13	13	17	19	19
C	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3	10.3	13	13	17	19	19
E	1.0	1.3	2.2	2.2	2.2	3.1	3.1	4.5	4.5	4.4	4.4	6.4	6.4	6.4
L	5.4	5.4	5.4	7.7	10.5	10.5	12.5	10.5	12.5	13.5	16.5	16.5	16.5	21.5
H				0.5~0.8				0.8 ~ 1.1				1.1~1.4		

三、技术性能 Specifications

项目 Items	特性 Characteristics							
工作温度范围 Operating Temperature Range	-40°C ~ 105°C							
额定电压范围 Rated Voltage Range	4V ~ 50V							
标称电容量范围 Nominal Capacitance Range	0.1 ~ 8200 μF							
标称电容量允许偏差 Nominal Capacitance Tolerance	±20% (20°C, 120Hz)							
漏电流 Leakage Current	$I \leq 0.01C_R V_R$ or $3(\mu A)$, 取较大者 (施加额定电压 2 分钟) C_R : 标称电容量 (μF) U_R : 额定电压 (V) $I \leq 0.01C_R V_R$ or $3(\mu A)$) Whichever is greater(After 2 minutes' application of rated voltage C_R : Nominal Capacitance (μF) U_R : Rated voltages (V)							
损耗角正切 (tgδ) Dissipation Factor (Max) 20°C, 120Hz	U_R (V)	4	6.3	10	16	25	35	50
	$tg\delta$	0.35	0.28	0.24	0.20	0.16	0.14	0.12
	容量大于 1000uF 者, 每增加 1000uF, 其损耗角正切值增加 0.02 When nominal capacitance exceeds 1000uF, add 0.02 to the value above for each 1000uF increase							


四、称电容量、额定电压、额定纹波电流与外形尺寸对应表

Nominal capacitance, rated voltage, rated ripple current and case size table

μF	4		6.3		10		16		25		35		50	
	DxL mm	I~ mA												
0.1													4x5.4	2.3
0.22													4x5.4	3.4
0.33													4x5.4	4.1
0.47													4x5.4	5
1.0													4x5.4	10
2.2													4x5.4	16
3.3											4x5.4	13	4x5.4	16
4.7							4x5.4	22	4x5.4	22	4x5.4	16	5x5.4	23
10							4x5.4	28	4x5.4	22	4x5.4	22	5x5.4	25
									5x5.4	28	5x5.4	30	6.3x5.4	32
22			4x5.4	29	4x5.4	28	4x5.4	28	5x5.4	32	6.3x5.4	60	6.3x5.4	35
					5x5.4	30	5x5.4	39	6.3x5.4	55			6.3x7.7	51
33	4x5.4	31	4x5.4	30	4x5.4	29	5x5.4	35	6.3x5.4	65	6.3x5.4	60	6.3x7.7	70
			5x5.4	34	5x5.4	34			6.3x5.4					
47	4x5.4	31	4x5.4	32	4x5.4	30	5x5.4	45	6.3x5.4	70	6.3x5.4	65	6.3x7.7	80
			5x5.4	46	5x5.4	45	6.3x5.4	70						
100	5x5.4	55	5x5.4	52	5x5.4	50	6.3x5.4	70	6.3x7.7	100	6.3x7.7	90	8x10.5	230
			6.3x5.4	71	6.3x5.4	69	6.3x7.7	120			8x10.5	296		
150	6.3x5.4	95	6.3x5.4	90	6.3x5.4	70	6.3x7.7	120	8x10.5	280	8x10.5	300	10x10.5	300
220	6.3x5.4	100	6.3x5.4	95	6.3x5.4	95	6.3x7.7	120	8x10.5	320	8x10.5	320	10x10.5	375
			6.3x7.7	120	6.3x7.7	120	8x10.5	280			10x10.5	435		
330	6.3x7.7	140	6.3x7.7	130	6.3x7.7	130	8x10.5	305	10x10.5	450	10x10.5	450	10x10.5	400
			8x10.5	290	8x10.5	305			10x10.5					
470	6.3x7.7	150	6.3x7.7	140	6.3x7.7	140	8x10.5	340	10x10.5	490	10x10.5	480	12.5x13.5	490
			8x10.5	330	8x10.5	340			10x10.5					
680	8x10.5	340	8x10.5	335	10x10.5	380	10x10.5	450	10x10.5	500	12.5x13.5	600	16x16.5	750
1000	8x10.5	350	8x10.5	340	10x10.5	410	10x10.5	550	12.5x13.5	550	16x16.5	800	18x16.5	990
1500	10x10.5	500	10x10.5	475	12.5x13.5	600	12.5x13.5	650	12.5x16.5	650	16x16.5	900		
2200			12.5x13.5	680	12.5x13.5	680	16x16.5	900	16x16.5	900	18x16.5	1050		
3300			12.5x16	850	16x16.5	950	16x16.5	950	18x16.5	1150				
4700			16x16.5	1000	16x16.5	1000	18x16.5	1225	18x21.5	1300				
6800			18x16.5	1290	18x16.5	1290								
8200			18x21.5	1450	18x21.5	1450								

→ I=Rated ripple current (mA) (105°C, 120Hz) I=额定纹波电流 (mA) (105°C, 120Hz)

五、构造图及材料表 Frame drawing and materials



序号 No.	部件名称 Parts	材料名称 Material	主要供应厂家名称 Main supply Factory
1	引出线	铝线 LG3+镀锡铜钢线 AL-wire LG3+Tin-plating of copper cover steel	全用电子有限公司 QUANYONG ELECTRONIC CO., LTD.
2	橡胶塞	丁基橡胶 IIR rubber	韩国 JCC JCC, Co. (KOREA)
3	PE 铝壳 PE-CASE	99.5%纯度铝 AL-99.5%	韩国 DN DN CO.(KOREA)
4	阳极箔 AL-foil(+)	99.99%或 99.98%形成 铝箔 Formed AL 99.98% or 99.98%	日本 JCC 公司 JCC Co. (JAPAN)
5	阴极箔 AL-foil(-)	99.7%铝箔 Etched AL 99.7%	韩国 JCC 公司 JCC Co. (KOREA)
6	电解纸 Separstor paper	电解电容器纸 Electrolytic Capacitor paper	日本 NKK 公司 NNK Co.(Japan)
7	座板 BASE	PPS	韩国 JS 公司 JS Co.(KOREA)

六、试验方法及要求 Tests

1	系列号(SERIES)	CDVT 系列(CDVT SERIES)																								
2	额定电压 (rated voltage)	4~50V																								
3	工作温度范围 Operating temperature range operating	<p>工作温度范围是指电容器在额定电压下能持续工作的所允许外部环境的温度范围</p> <p>operating temperature range is the range of ambient temperature at which the capacitor can be operated continuously at rated voltage</p> <p>SPEC:-40~+105°C</p>																								
4	电容容量 capacitance	测量等效电路图 measuring circuit equivalent series circuit																								
		测量温度 20°C		measuring temperature																						
		测量频率 120HZ		measuring frequency																						
		测量电压 0.5Vrms		measuring voltage																						
		标称电容量允许偏差: $\pm 20\%$ MAX		Nominal Capacitance Tolerance: $\pm 20\%$ MAX																						
5	损耗角正切 tangent of the loss angle	<p>损耗角正切的测量应要和测量电容量一样的条件下进行</p> <p>Measurement should be made under the same conditions as those given for the measurement of capacitance</p> <p>SPEC:</p> <table border="1"> <thead> <tr> <th>损耗角正切 (tgδ)</th> <th>UR (V)</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> </thead> <tbody> <tr> <td>tgδ</td> <td>0.35</td> <td>0.28</td> <td>0.24</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> </tr> </tbody> </table>								损耗角正切 (tgδ)	UR (V)	4	6.3	10	16	25	35	50	tgδ	0.35	0.28	0.24	0.20	0.16	0.14	0.12
损耗角正切 (tgδ)	UR (V)	4	6.3	10	16	25	35	50																		
tgδ	0.35	0.28	0.24	0.20	0.16	0.14	0.12																			
6	<p>将额定电压加在电容和 1000±100Ω 的保护电阻上。在充电 2 分钟后，按下列等式计算漏电流</p> <p>the rated voltage shall be applied across the capacitor and its protective resistor which shall be 1000±100Ω. The leakage current shall be then measured after an electrifications period of (A)min. The leakage current shall be calculated by the following equation</p> <p>在加上额定电压一定时间后， 应满足下列要求: $I \leq 0.01CV$ or $3\mu A$ Which is greater(取较大者) (20°C, 2 分钟)</p> <p>SPEC: The following specifications shall be satisfied when the rated voltage is applied for the required time.</p>																									
7	允许最大纹波电流 Maximum permissible ripple current	<p>在规定的某一频率下的最大交流电流，在该电流下电容器连续工作。即使在测过第 16 项下的耐久性后，此要求仍要满足。在此，DC 电压加上最大纹波电压小于等于额定电压。</p> <p>The maximum sinusoidal alternating current of a frequency specified below, at which the capacitor can be operated continuously. This requirement shall be satisfied even after the measurement of clause 16(electrical endurance) Where $(DC\ voltage + peak\ ripple\ voltage) \leqslant rated\ voltage$</p>																								

接上表

		步骤 step							温度 temperature		持续时间 Duration																									
8	温度特性 Characteristics of temperature								20±2°C		15 分钟 15 min																									
									最低工作温度 minimum operating temperature		2 小时 2 hours																									
									20±2°C		15 分钟 15 min																									
									最高工作温度 maximum operating temperature		2 小时 2 hours																									
									步骤 1: 测量容量, 损耗角正切和阻抗 Step1: Capacitance, tangent of the loss angle impedance shall be measured.																											
									步骤 2: 在电容器存放 2 小时后, 测量容量, 损耗角正切和阻抗 Step2: After the capacitor being stored for 2hours, Capacitance, tangent of the loss angle and impedance shall be measured.																											
									步骤 3: 电容器在 20±2°C 下存放 15 分钟 Step3: The capacitor being stored fro 15min at20±2°C																											
									步骤 4: 在电容器存放 2 小时后, 测量容量和漏电流。 Step4: After the capacitor being stored for 2hours, capacitance and leakage current shall be measured																											
									<table border="1"> <thead> <tr> <th>额定电压 rated voltage</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> </thead> <tbody> <tr> <td>Z(-25°C/Z(+20°C)</td> <td>7</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z(-40°C/Z(+20°C)</td> <td>15</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> </tr> </tbody> </table>				额定电压 rated voltage	4	6.3	10	16	25	35	50	Z(-25°C/Z(+20°C)	7	4	3	2	2	2	2	Z(-40°C/Z(+20°C)	15	8	6	4	4	3	3
额定电压 rated voltage	4	6.3	10	16	25	35	50																													
Z(-25°C/Z(+20°C)	7	4	3	2	2	2	2																													
Z(-40°C/Z(+20°C)	15	8	6	4	4	3	3																													
9	浪涌测试 Surge test								在规定温度下, 循环测试 1000 次, 每次充电 30±5 秒, 在放电大约 5 分 30 秒。在标准温度条件下存放使其稳定, 然后测试。 The capacitor shall be subjected to 1000cycles at a temperature specified below, each consisting of a charge period of 30±5sec, followed by a discharge period of approx. 5min30sec. And the capacitor shall be stored under standard conditions thermal to obtain stability, after which measurements shall be made.																											
									measurement circuit(测试电路图)																											
									VS: 浪涌电压 Surge voltage		V1: 直流电压 DC voltmeter																									
									R1: 保护电阻 (1KΩ) Protective series resistor		R2: 放电电阻器 Discharge resistor																									
									CX: 测试电容 Test capacitor		S: 开关 Switch																									
									SPEC: 1) $\Delta C/C \leq 15\%$ 2) $\operatorname{tg} \delta <$ 规定值 3) 电压																											
									<table border="1"> <thead> <tr> <th>RATED VOLTAGE(V_{DC})</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> </thead> <tbody> <tr> <td>SURGE VOLTAGE(V_{DC})</td> <td>5</td> <td>8</td> <td>13</td> <td>20</td> <td>32</td> <td>44</td> <td>63</td> </tr> </tbody> </table>				RATED VOLTAGE(V _{DC})	4	6.3	10	16	25	35	50	SURGE VOLTAGE(V _{DC})	5	8	13	20	32	44	63								
RATED VOLTAGE(V _{DC})	4	6.3	10	16	25	35	50																													
SURGE VOLTAGE(V _{DC})	5	8	13	20	32	44	63																													

接上表

10	端子强度 Terminal strength	<p>1) 拉力(tensile)</p> <table border="1" data-bbox="463 294 1446 473"> <thead> <tr> <th>d(mm)</th><th>[N]</th><th>Duration time</th></tr> </thead> <tbody> <tr> <td>0.3< d≤0.5</td><td>5</td><td rowspan="3">10±2sec(秒)</td></tr> <tr> <td>0.5< d≤0.8</td><td>10</td></tr> <tr> <td>0.8< d≤1.25</td><td>20</td></tr> </tbody> </table> <p>2) 抗弯强度 (Bending) 端子应该在每一方向上折弯一次，总共两次 The terminal shall be subjected to 1 bend in each direction to give a total 2 bends.</p> <table border="1" data-bbox="463 601 1446 765"> <thead> <tr> <th>d(mm)</th><th>[N]</th></tr> </thead> <tbody> <tr> <td>0.3< d≤0.5</td><td>2.5 (0.25KG)</td></tr> <tr> <td>0.5< d≤0.8</td><td>5.0 (0.51KG)</td></tr> <tr> <td>0.8< d≤1.25</td><td>10.0(1.0KG)</td></tr> </tbody> </table> <p>端子没有破损或松动 SPEC: No breaking and loosening of terminal</p>	d(mm)	[N]	Duration time	0.3< d≤0.5	5	10±2sec(秒)	0.5< d≤0.8	10	0.8< d≤1.25	20	d(mm)	[N]	0.3< d≤0.5	2.5 (0.25KG)	0.5< d≤0.8	5.0 (0.51KG)	0.8< d≤1.25	10.0(1.0KG)
d(mm)	[N]	Duration time																		
0.3< d≤0.5	5	10±2sec(秒)																		
0.5< d≤0.8	10																			
0.8< d≤1.25	20																			
d(mm)	[N]																			
0.3< d≤0.5	2.5 (0.25KG)																			
0.5< d≤0.8	5.0 (0.51KG)																			
0.8< d≤1.25	10.0(1.0KG)																			
11	可焊性 solderability	<p>焊料(Solder) : H60A. H60S or(或)H63A 焊接温度(Solder temperature) : 245±2°C 浸入时间(Immersion time) : 3±0.5sec(秒) 浸入深度(Immersion depth) : 2mm 熔化: 松香在酒精的浓度是 25% Flux: 25% by weight of rosin in ethanol 从含浸处到顶部, 至少要有 3/4 的部分覆盖有新焊料 SPEC: 1) 3/4 of the circumference of the surface up to the immersed shall be covered with new solder.</p>																		
12	耐焊接热 Resistance to soldering heat	<p>焊料(Solder) : H60A. H60S or(或)H63A 焊槽温度(Solder temperature) : 260±5°C (or 或 350±10°C) 浸入时间(Immersion time) : 10±1sec(秒) (or 或 3.5±0.5sec) 绝热屏蔽板的厚度 (Thickness of heat shunt:1.6mm) : 1.6mm SPEC: 1) 电容量变化 Change in capacitance: ±10% 初始值以内 Within±10% of the initial value 2) 损耗角正切 tangent of the loss angle: 小于等于初始规定值 The initial specified value or less 3) 漏电流 leakage current: 小于等于初始规定值 The initial specified value or less</p>																		
13	抗振性 Vibration	<p>试验电容器的耐振性。在整个频率范围内, 从 10 赫兹到 55 赫兹, 然再返回到 10 赫兹, 就这样在一分钟内往返循环。振幅为 1.5mm。在三个垂直方向上, 每一方向要持续 2 小时, 总共 6 小时 Only endurance conditioning by sweeping shall be made. The entire frequency range, from 10 to 55Hz and return to 10Hz, shall be transversed in 1min. Amplitude(total excursion)1.5mm, This motion shall be applied for a period of 2hours in each of 3 mutually perpendicular directions(a total of 6 hours) SPEC: 1) 电容量的变化(change in capacitance) : ±5% 初始值以内 (within ±5% of the initial value) 2) 无可见损伤(No visible damage)</p>																		

接上表


14	稳态湿热 Damp heat	<p>电容器要在温度 $40\pm2^{\circ}\text{C}$, 相对湿度 90% 到 95% 条件下存放 240 ± 8 个小时。然后在标准条件下放 1 到 2 小时后进行测量。</p> <p>the capacitor shall be stored at a temperature of $40\pm2^{\circ}\text{C}$ and relative humidity of 90 to 95% for 240 ± 8 hours. And then the capacitor shall be subjected to standard atmospheric conditions for 1 to 2 hours, after which measurements shall be made</p> <p>SPEC:1) 电容量的变化 change in capacitance: $\pm15\%$ 初始值以内 within $\pm15\%$ of the initial value;</p> <p>2) 损耗角正切 tangent of loss angle: 小于等于初始规定值 The initial specified value or less;</p> <p>3) 漏电流 leakage current: 小于等于初始规定值 The initial specified value or less</p>
15	高温储存 shelf life	<p>在 105°C 温度下不外加电压贮存, 电容器存放 1000 小时。然后在标准条件下放 1 到 2 小时后进行测量, 并且在测漏电流前, 必须满足下列条件。The capacitor shall be stored at 105°C temperature specified below for 1000 hours. During which time no voltage shall be applied. And then the capacitor shall be subjected to standard atmospheric conditions for 1 to 2 hours, after which measurements shall be made, Prior to the measurement of leakage current, following conditioning may be made.</p> <p>SPEC:1) 电容量的变化 change in capacitance: $\pm20\%$ 初始值以内 within $\pm20\%$ of the initial value; ($\leq 16V: \pm25\%$ 初始值以内) ($\leq 16V: \text{within } \pm25\%$ of the initial value);</p> <p>2) 损耗角正切 tangent of loss angle: $\pm200\%$ 初始规定值以内 within $\pm200\%$ of the initial value;</p> <p>3) 漏电流 leakage current: 小于等于初始规定值 The initial specified value or less</p>
16	耐久性 load life	<p>在 $105\pm2^{\circ}\text{C}$ 下, 电容器加额定电压 1000 小时。在标准条件下放 1 到 2 小时后进行测量。The rated voltage shall be applied continuously to the capacitor at maximum operating temperature $105\pm2^{\circ}\text{C}$ for 1000 hours. And then the capacitor shall be subjected to standard atmospheric conditions for 1 to 2 hours, after which measurement shall be made.</p> <p>SPEC:1) 电容量的变化 change in capacitance: $\pm20\%$ 初始值以内 within $\pm20\%$ of the initial value; ($\leq 16V: \pm25\%$ 初始值以内) ($\leq 16V: \text{within } \pm25\%$ of the initial value);</p> <p>2) 损耗角正切 tangent of loss angle: $\pm200\%$ 初始规定值以内 within $\pm200\%$ of the initial value;</p> <p>3) 漏电流 leakage current: 小于等于初始规定值 The initial specified value or less</p>

七、标志 Marking (见外形图及尺寸表)

说明：标识中的“VT”是红太洋实业(深圳)有限公司 CDVT 型贴片产品的系列标识。

片式铝电解电容的编带 V- Chip Type Aluminum Electrolytic Capacitors


编带 Carrier tape



$\Phi D \times L$	4x5.4	5x5.4	6.3x 5.4	6.3x 7.7	6.3* 10.5	8x 10.5	8x 12.5	10x 10.5	10x 12.5	12.5x 13.5	12.5x 16.5	16x 16.5	18x 16.5	18x 21.5	(mm)
W	12.0	12.0	16.0	16.0	16.0	24.0	24.0	24.0	24.0	32.0	32.0	44.0	44.0	44.0	
P	8.0	12.0	12.0	12.0	12.0	16.0	16.0	16.0	16.0	24.0	24.0	28.0	32.0	32.0	
F	5.5	5.5	7.5	7.5	7.5	11.5	11.5	11.5	11.5	14.2	14.2	20.2	20.2	20.2	
A ₀	5.0	6.0	7.0	7.0	7.0	8.7	8.7	10.7	10.7	13.2	13.2	17.5	19.5	19.5	
B ₀	5.0	6.0	7.0	7.0	7.0	8.7	8.7	10.7	10.7	13.2	13.2	17.5	19.5	19.5	
T ₂	5.8	5.8	5.8	8.0	11.0	11.0	13.3	11.0	13.3	14.3	17.3	17.3	17.8	22.5	

■ 编
带
包

装盘 Reel



■ Package quantity 包装数量

$\Phi D \times L$	Quantity / Reel 数量 / 每盘	pcs/ Small packing box 数量/小包装箱	pcs/Large packing box 数量/大包装箱
4×5.4	2000pcs	24000pcs	48000pcs
5×5.4	1000pcs	12000pcs	24000pcs
6.3×5.4、6.3×7.7、8×6.5	1000pcs	10000pcs	20000pcs
8×10.5、10×10.5	500pcs	3500pcs	7000pcs
6.3×10.5	800pcs	8000pcs	16000pcs
8×12.5	400pcs	2800pcs	5600pcs
10×12.5	400pcs	2800pcs	5600pcs
12.5×13.5	250pcs	2500pcs	5000pcs
12.5×16.5	200pcs	800pcs	1600pcs
16×16.5	200pcs	800pcs	1600pcs
18×16.5	175pcs	700pcs	1400pcs
18×21.5	125pcs	500pcs	1000pcs

CDVT 型产品承认书

参数 项目	电压: 10 V	容量: 100 uF	容量误差: 土20%	温度范围: -40°C~+105°C						
	外型尺寸 直径 D: <u>6.3 mm</u> 高度 L: <u>5.4+0.3-0.3mm</u> 脚距: <u>2.5 mm</u>									
性能	电容量 (C) : <u>80</u> ~ <u>120</u> (uF) 损失 (tgδ) : <u>24</u> % (Max) 漏电 (I) : <u>10</u> uA (Max)									
贮存试验	(105°C 2000 小时试验后)		容量变化率: 土20%初始值以内 (≤16 V: 土25% 初始值以内) 损失值 ≤ 200%初始规定值 漏电流 ≤ 初始规定值							
寿命试验	(105°C 2000 小时试验后)		容量变化率: 土20%初始值以内 (≤16V: 土25% 初始值以内) 损失值 ≤ 200%初始规定值 漏电流 ≤ 初始规定值							
初始测试(25±3°C)										
No.	1	2	3	4	5	6	7	8	9	10
C	94.6	95.2	94.3	94.8	94.9	94.7	94.2	94.4	95.7	95.6
tgδ %	9.34	9.75	9.53	9.58	9.62	9.57	9.64	9.58	9.68	9.61
LC	0.86	0.92	0.87	0.93	0.95	0.97	0.99	1.08	0.96	1.02
制样: 赵美利			审核: 施华			批准: 黄应明				
结 论:					客户承认章: 客户签发_____ 年 月 日					
1. <input type="checkbox"/> 承 认 2. <input type="checkbox"/> 有 条 件 承 认 3. <input type="checkbox"/> 退 料										

参数 项目	电压: 10V	容量: 220 uF	容量误差: ±20%	温度范围: -40°C~+105°C						
外型尺寸	直径 D: <u>6.3 mm</u> 高度 L: <u>5.4±0.3mm</u> 脚距: <u>2.5 mm</u>									
性能	电容量 (C) : <u>176 ~ 264</u> (uF) 损失 (tgδ) : <u>24</u> %(Max) 漏电 (I) : <u>22</u> uA (Max)									
贮存试验	(105°C 2000 小时试验后)									
寿命试验	(105°C 2000 小时试验后)									
初始测试(25±3°C)										
No.	1	2	3	4	5	6	7	8	9	10
C	198.6	203.5	204.9	206.1	205.7	204.3	207.2	204.1	203.1	204.7
tgδ %	14.6	14.2	14.1	14.6	14.3	14.7	14.2	14.3	13.8	14.5
LC	2.2	2.4	2.3	2.1	2.6	2.4	2.3	2.2	2.4	2.5
制样:	赵美利		审核:	施华		批准:	黄应明			
结论:	客户承认章: 1. <input type="checkbox"/> 承认 2. <input type="checkbox"/> 有条件承认 3. <input type="checkbox"/> 退料				客户签发_____ 年 月 日					

参数 项目	电压: 10 V	容量: 470 uF	容量误差: ±20%	温度范围: -40°C ~ +105°C						
外型尺寸	直径 D: <u>8 mm</u> 高度 L: <u>10.5+0.5-0.5 mm</u> 脚距: <u>3.5 mm</u>									
性能	电容量 (C) : <u>376 ~ 564</u> (uF) 损失 (tgδ) : <u>24</u> % (Max) 漏电 (I) : <u>47</u> uA (Max)									
贮存试验	(105°C 2000 小时试验后)									
寿命试验	(105°C 2000 小时试验后)									
初始测试(25±3°C)										
No.	1	2	3	4	5	6	7	8	9	10
C	435.2	442.1	438.7	436.4	432.3	437.8	431.5	433.6	432.8	433.1
tgδ %	11.2	10.8	11.5	11.3	11.4	11.0	11.7	11.2	11.6	11.9
LC	4.6	4.7	4.9	5.2	4.3	5.8	5.9	5.2	5.7	5.6
制样:	赵美利	审核:	施华	批准:	黄应明					
结论:	客户承认章: 1. <input type="checkbox"/> 承认 2. <input type="checkbox"/> 有条件承认 3. <input type="checkbox"/> 退料				客户签发_____	年 月 日				